



TACTICAL PATROL SLING

OPERATOR MODEL: OPERATION AND INSTALLATION GUIDE

Congratulations! You are now the owner of one of the most versatile slings available for a wide variety of long guns, rifles, and shotguns for civilian, military, or law enforcement use. Guaranteed against failure under normal wear and tear, this is literally the last sling you will ever buy!

The **Tactical Patrol Sling** (TPS) provides the operator with several options and configurations for use with numerous style long guns in diverse shooting environments. Designed for both right and left handed shooters, this sling is ambidextrous ready out of the box – no need to change sling components for left-handed operators.

Utilizing H&K style clip connectors and quick release slide buckles, the TPS converts from a single to two point attachment harness in seconds allowing the operator to customize the sling from routine daily use to specialized operational needs quickly. The addition of a rubberized shoulder pad allows the operator for comfort and exact placement every time the operator puts it on.

Manufactured using military specification (Mil Spec) 4088 one inch Type II webbing with a breaking strength of 600 pounds, triple stitched for added security against breaking failure, these slings are guaranteed to hold-up in real world fighting environments under the harshest conditions.

SLING COMPONENTS

Weapon Attachment Strap – Attaches the sling to the weapon. The quick release slide buckle allows for quick removal of the weapon system from the main sling without removal of the entire sling from the operator's body.

Shoulder Sling Portion – Is the attachment portion for all sling portions and attachments and has a rubberized shoulder pad for operator comfort, to prevent sling movement, and to insure exact placement every time the weapon is mounted.

Expandable Bungee Portion – Built into the shoulder sling portion, this allows for rapid sling expansion and comfort when pushing out or transitioning from dominant to non-dominant side shooting.

Adjustment D-Ring Strap – Designed to be manipulated with the non-trigger hand, this allows the operator to adjust both tension and size of the sling to the contour and comfort demands of the operator's body.

Secondary Point/Sling Attachment Portion – Attaches shoulder sling portion to weapon attachment strap. Also allows for rapid conversion from single point sling system to two-point sling system with a click of the H&K style connector.

Picture of sling goes here and part identification / nomenclature

MOE'S MEASURES, LLC. - TACTICAL DIVISION

"Making tactical gear better."



TACTICAL PATROL SLING

OPERATOR MODEL: OPERATION AND INSTALLATION GUIDE

DONNING INSTRUCTIONS FOR TACTICAL PATROL SLING

1. With one hand, hold sling chest high in front of operator.
2. Position sling so weapon attachment strap is pointed towards ground between operator's feet.
 - If right handed shooter, adjustment D-Ring strap should be on operator's left side. If left handed shooter, adjustment D-Ring strap should be operator's right side.
3. Place head through large circle portion of sling.
 - If right handed shooter, place left arm through large circle portion so adjusting rubberized shoulder pad so it lays next to neck across shoulder on right side of head.
 - If left handed shooter, place right arm through sling adjusting rubberized shoulder pad so it lays next to neck across shoulder on left side of head.

STEP 1



SINGLE POINT INSTALLATION INSTRUCTIONS

STEP 2



1. With sling on operator, grasp H&K style connector on end of **Weapon Attachment Strap**.
2. Attach H&K style connector to long gun's single connection point on non-trigger side of weapon*
3. Using non-trigger hand, reach to side of operator's body and grasp end of **Adjustment D-Ring Strap** and pull down to adjust strap for comfort and fit and prepare to engage for action!

STEP 1



TWO POINT INSTALLATION INSTRUCTIONS

STEP 2



1. Once sling is on operator, attach H&K style connector on end of **Weapon Attachment Strap** to long gun connection point*
2. Disconnect H&K style connector from **Secondary Point / Sling Attachment Portion** and connect to second weapon attachment point.
3. Using non-trigger hand, reach to side of operator's body and grasp end of **Adjustment D-Ring Strap** and pull down to adjust strap for comfort and fit and prepare to engage for action!

**FOR ADVANCED INSTRUCTIONS OR TO LOOK AT
ADDITIONAL SLING MODELS AND OUR OTHER
TACTICAL OR PUBLIC SAFETY GEAR, VISIT OUR
WEBSITE AT WWW.MOESMEASURES.COM**

MOE'S MEASURES, LLC. - TACTICAL DIVISION
"Making tactical gear better."